


**SPECIFICATIONS**

<b>DIMENSIONS</b>	D80mm x H89mm
<b>CUT OUT</b>	Ø 75mm
<b>COLOUR TEMP</b>	3000K Warm White
<b>CRI</b>	97
<b>LIFESPAN</b>	55,000 Hours L90(10k) TM-21
<b>BEAM ANGLE</b>	50°
<b>INTENSITY AT 2M</b>	329 lux / 1.9m Beam Width from 2m Height
<b>INTENSITY AT 3M</b>	146 lux / 2.8m Beam Width from 3m Height
<b>MATERIAL</b>	Aluminum , coated optic glass
<b>IP RATING</b>	IP44
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired)
<b>INSTALLATION</b>	Cut holes with extra caution (5mm rim)
<b>APPLICATION</b>	Interior residential downlighting
<b>WARRANTY</b>	5 Year Warranty

**922**  
LUMENS

**11**  
WATTS

**AC**  
240V

 UID™ Dimmable Under  
 Insulation Driver Included

**COLOUR PARAMETERS**

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg
3000K	97.6	93.9	94..9	101.0

**AVAILABLE IN**

DESCRIPTION	CODE
White 3000K	R530 W3K
Black 3000K	R530 B3K