



SPECIFICATIONS

DIMENSIONS	D105 x H80mm
CUT OUT	Ø 82mm
COLOUR TEMP	3000K Warm White
CRI	90
LIFESPAN	50,000 Hours
BEAM ANGLE	60°
TILT ANGLE	30° (Complete with patented IP44 tilt gasket)
MATERIAL	316 Stainless Steel with Silicon Gasket
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC Rated
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired), 260mA
APPLICATION	Exterior
COMPLETE WITH	Silicon Gasket
WARRANTY	5 Year Warranty

880 LUMENS	9.5 WATTS	AC 240V
-------------------	------------------	----------------

	UID™ Dimmable Under Insulation Driver Included
--	--

RETROFIT
 Fits 82mm Cut Outs

AVAILABLE IN

DESCRIPTION	CODE
Black 316 STS 3000K	R737 KBSSWUDL
Silver 316 STS 3000K (CRI80, 800lm)	R737 KSSWUDL
White 316 STS 3000K	R737 KWSSWUDL

OPTIONAL ACCESSORIES

DESCRIPTION	CODE
155mm 316 STS Conversion Plate Black	R737 CPSSB
155mm 316 STS Conversion Plate White	R737 CPSSW

