



SPECIFICATIONS

DIMENSIONS	D86 x H95mm
CUT OUT	Ø 72mm
COLOUR TEMP	3000K Warm White
CRI	90
LIFESPAN	50,000 Hours
BEAM ANGLE	60°
MATERIAL	Aluminium
IP RATING	IP44
CLEARANCE	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
CLASSIFICATION	IC Rated
APPLICATION	Residential / Commercial Interior
DRIVER	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 260mA
WARRANTY	5 Year Warranty

850 LUMENS	9.5 WATTS	AC 240V
-----------------------	----------------------	--------------------

	UID™ Dimmable Under Insulation Driver Included
--	--



AVAILABLE IN

DESCRIPTION	CODE
White 3000K	R763 KWWUDL
White Sunset Dim 3000-2000K, CRI95, 550lm	R763 KWCUDL
Brushed Chrome 3000K	R763 KBCWUDL
Silver 3000K	R763 KSWUDL
Black 3000K	R763 KBWUDL

ACCESSORIES

DESCRIPTION	CODE
R763 Mini Downlight Recessed Trimless Plaster Mould 72mm C/O 86mm O/D	R763 PB13



PB13 Recessed Plaster Mouldings set the downlight back into the ceiling space. Once finished the setback creates a perfectly flat ceiling line with "invisible" downlights. Halcyon recessed plaster mouldings create an extra low glare lighting effect for the ultimate lighting ambience and add an extra finishing touch to all high end installations.
Pictured: R763 PB13 & R763 KWWUDL Downlight