

Exterior Commercial Recessed Fixed Downlight XL Low Glare <25.5W

R836



SPECIFICATIONS

DIMENSIONS

D220mm x H130mm




R836 PH Optional Accessory
for Concrete Installations

| | |
|-----------------------|---|
| CUT OUT | Ø 200mm |
| COLOUR TEMP | 4000K Natural White |
| LUMENS | Multi Output fitting At 700mA = 25.5W / 2600lm At 500mA = 18W / 1857lm |
| CRI | 90 |
| LIFESPAN | 50,000 Hours (L70) |
| BEAM ANGLE | 40° Standard (12°, 20° & 70° accessories available) |
| CUT OFF ANGLE | 30° |
| MATERIAL | Aluminum Safety glass |
| IP RATING | IP65 |
| IK RATING | IK08 |
| CLEARANCE | 100mm from rear of heatsink to building elements |
| CLASSIFICATION | Non-IC Rated |
| DRIVER | Not included, choose from Halcyon 700mA or 500mA Standard, Dimmable or Dali range |
| APPLICATION | Exterior Commercial and Residential downlighting |
| WARRANTY | 5 Year Warranty |

<2600
LUMENS

<25.5
WATTS

<700mA
SERIES CC



Driver sold separately,
specify when ordering.

AVAILABLE IN

| DESCRIPTION | CODE |
|-------------------------------------|---------|
| Black, 4000K (Driver not included) | R836 B4 |
| White, 4000K (Driver not included) | R836 W4 |
| Silver, 4000K (Driver not included) | R836 S4 |

ACCESSORIES

| DESCRIPTION | CODE |
|--|---------|
| 12 Degree Reflector | R836 12 |
| 20 Degree Reflector | R836 20 |
| 70 Degree Reflector | R836 70 |
| Frosted Glass cover | R836 FG |
| Honeycomb Glare Reducer | R836 HC |
| Plastic installation housing for concrete castings (see diagram) | R836 PH |