

**SPECIFICATIONS**

|                       |   |
|-----------------------|---|
| <b>DIMENSIONS</b>     | <i>D165 x H137mm</i>  |
| <b>CUT OUT</b>        | <i>Ø 150mm</i>  |
| <b>COLOUR TEMP</b>    | <i>3000K Warm White or 4000K Natural White</i>                |
| <b>LUMENS</b>         | <i>3000K Warm White 2870lm<br/>4000K Natural White 2888lm</i> |
| <b>CRI</b>            | <i>90</i>   |
| <b>LIFESPAN</b>       | <i>40,000 Hours</i>   |
| <b>BEAM ANGLE</b>     | <i>70°</i>  |
| <b>MATERIAL</b>       | <i>Aluminium</i>  |
| <b>IP RATING</b>      | <i>IP54</i>   |
| <b>CLEARANCE</b>      | <i>50mm from rear of heatsink to building elements</i>        |
| <b>CLASSIFICATION</b> | <i>NON IC Rated</i>   |
| <b>DRIVER</b>         | <i>900mA (Sold Separately)</i>                                |
| <b>APPLICATION</b>    | <i>Commercial Interior</i>                                    |
| <b>WARRANTY</b>       | <i>5 Year Warranty</i>  |

**<2888  
LUMENS****34  
WATTS****900<sub>mA</sub>  
SERIES CC**Driver sold separately,  
specify when ordering.**AVAILABLE IN**

| DESCRIPTION               | CODE     |
|---------------------------|----------|
| White 3000K (Indent only) | R853 WWL |
| White 4000K               | R853 WNL |

**ACCESSORIES**

| DESCRIPTION   | CODE    |
|---------------|---------|
| 12° Reflector | R853 12 |
| 20° Reflector | R853 20 |
| 40° Reflector | R853 40 |