



SPECIFICATIONS

| | |
|-----------------------|---|
| DIMENSIONS | D100 x H67mm |
| CUT OUT | Ø 92mm |
| COLOUR TEMP | 3000K Warm White or 4000K Natural White |
| CRI | 90 |
| LIFESPAN | 40,000 Hours |
| BEAM ANGLE | 50° |
| TILT ANGLE | 45° |
| ROTATE ANGLE | 355° |
| MATERIAL | Aluminium |
| CLEARANCE | 25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements. |
| CLASSIFICATION | IC Rated |
| DRIVER | DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired) 350mA |
| APPLICATION | Residential / Commercial Interior |
| WARRANTY | 5 Year Warranty |

**1200
LUMENS**

**13
WATTS**

**AC
240V**



UID™ Dimmable Under Insulation Driver Included



R866's are supplied with a Prismatic Lens installed as standard (1) Optional clear lens is also included in each downlight kit (2)

AVAILABLE IN

| DESCRIPTION | CODE |
|-------------|-----------|
| Black 3000K | R866 B3UK |
| Black 4000K | R866 B4UK |
| White 3000K | R866 W3UK |
| White 4000K | R866 W4UK |