



### SPECIFICATIONS

<b>DIMENSIONS</b>	D112 x H88mm
<b>CUT OUT</b>	Ø 100mm
<b>COLOUR TEMP</b>	3000K Warm White or 4000K Natural White
<b>LUMENS</b>	3000K Warm White or 1100lm 4000K Natural White 1200lm
<b>CRI</b>	90
<b>LIFESPAN</b>	40,000 Hours
<b>BEAM ANGLE</b>	50°
<b>TILT ANGLE</b>	+45° Down / -15° Up
<b>ROTATE ANGLE</b>	355°
<b>MATERIAL</b>	Aluminium
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	350mA (Sold Separately)
<b>APPLICATION</b>	Residential / Commercial Interior
<b>WARRANTY</b>	5 Year Warranty

<1200  
LUMENS

13  
WATTS

350mA  
SERIES CC



Driver sold separately,  
specify when ordering.



### ACCESSORIES

DESCRIPTION	CODE
20° Reflector	R867 20

### AVAILABLE IN

DESCRIPTION	CODE
White 3000K	R867 WWL
White 4000K	R867 WNL
Black 3000K	R867 BWL
Black 4000K	R867 BNL