



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)	
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Screw	Steel	M5\Zn Plated
3	Current carrier	Copper	Sn Plated
4	Cage	Steel	Zn Plated

REV	ECN	DESCRIPTION	DRAFT	DATE
1				

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/100	600/100	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特等	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/76	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N.m/Lb.in)	M5, 2.5/27		
线径范围(裸线/绞线)/Wire Range(rigid and flexible)(mm ² /AWG)	1.5~2.5/1.4~3(Str)		
间距/Pitch(mm)	12.0		
剥线长度/Stripping length(mm)	12~13		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

MATERIAL:	SURFACE:
MAT NO.:	/
STATUS:	/
APPD: Li GL 2020.05.25	NAME:
CHKD: Moo J 2020.05.25	DC16-01P-1Y-00A(H)
DRAFT:Wang LX 2020.05.25	DRAWING NO.:
	DC16-C01
	TYPE: CUSTOMER DRAWING
	SCALE: 1:1
	REV
	TO-2
	1/1

DEGSON[®] NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司