

## Product data sheet

### Characteristics

# PDL56SPO310RO

Pendant Socket, 10A, 250V, 3-Flat Pin,  
Resistant Orange



### Main

Range of product	56 Series™
Product or component type	Socket-outlet
Material	PBT (polybutylene terephthalate)


### Complementary

Colour tint	Orange
Surface finish	Gloss
Rated current	10 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Motor M-rating AS3133	M50
Network number of phases	1 phase
Pin number	3
Device composition	Flat pin
Mounting mode	Pendant
IP degree of protection	IP66
Ambient air temperature for operation	-40...55 °C
Cable cross section	0.75...2.5 mm <sup>2</sup>
Quantity per set	Set of 4
Type of packing	Carton

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.218 kg
Package 1 Height	65 mm
Package 1 width	85 mm
Package 1 Length	170 mm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>

---

China RoHS Regulation

 [China RoHS Declaration](#)

---

Environmental Disclosure

 [Product Environmental Profile](#)

---