

Product data sheet
Characteristics

PDL100SA360
Motion Sensor PDL - Passive infrared -
Outdoor - 6m detection radius - 240 V - White



Main

Range of product	PDL Sensors
Product or component type	Sensor
Colour tint	White
Load type	1000 W incandescent 500 W fluorescent 600 W 12 V halogen 400 W motor
Quantity per set	Set of 1
Type of packing	Carton

Complementary

Rated voltage	220...240 V AC 50 Hz
Mounting support	Wall Conduit Ceiling
Mounting location	Corner





Environment

IP degree of protection	IP44
Ambient air temperature for operation	-20...40 °C

Packing Units

Package 1 Weight	0.336 kg
Package 1 Height	95.000 mm
Package 1 width	95.000 mm
Package 1 Length	145.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.